




Patent
7150289




Pre-Installed Swing/Drip Connections

- No tools, snaps or straps required
- Significantly less flow restriction than inserts
- Installs six times faster than inserts with worm screw clamps
- Superior versatility (remove, move, replace)


Installation Instructions



Simply snap saddle onto the pipe.



While holding components in position, place the tap onto the saddle.



Screw the tap onto the ratcheting lock until it can no longer turn.

Saddles	Description		
KT007C	3/4" PE	x	1/2" FPT
KT007D	3/4" PE	x	3/4" FPT
KT010C	1" PE	x	1/2" FPT
KT010D	1" PE	x	3/4" FPT
KT012C	1 1/4" PE	x	1/2" FPT
KT012D	1 1/4" PE	x	3/4" FPT
KT015C	1 1/2" PE	x	1/2" FPT
KT015D	1 1/2" PE	x	3/4" FPT
Saddles with Elbow	Description		
KT007SW-E	3/4" PE	x	Swing Elbow
KT010SW-E	1" PE	x	Swing Elbow
KT012SW-E	1 1/4" PE	x	Swing Elbow
KT015SW-E	1 1/2" PE	x	Swing Elbow
Saddles with Straight	Description		
KT007DMA17	3/4" PE	x	17mm Male Adaptor
KT007SW-S	3/4" PE	x	Swing Straight
KT010DMA17	1" PE	x	17mm Male Adaptor
KT010SW-S	1" PE	x	Swing Straight
KT012SW-S	1 1/4" PE	x	Swing Straight
KT015SW-S	1 1/2" PE	x	Swing Straight
Saddles	Description (Suits Metric Pipe)		
KT025C	25mm PE	x	1/2" FPT
KT025D	25mm PE	x	3/4" FPT
KT032C	32mm PE	x	1/2" FPT
KT032D	32mm PE	x	3/4" FPT
Saddles with Elbow	Description (Suits Metric Pipe)		
KT025SW-E	25mm PE	x	Swing Elbow
KT032SW-E	32mm PE	x	Swing Elbow
Saddles with Straight	Description (Suits Metric Pipe)		
KT025DMA17	25mm PE	x	17mm Male Adaptor
KT025SW-S	25mm PE	x	Swing Straight
KT032DMA17	32mm PE	x	17mm Male Adaptor
KT032SW-S	32mm PE	x	Swing Straight

Sold in Quantities: 10 Per Bag – 200 Units Per Box

Specifications		H	W	L	
Measurements	KT007 C and D	2" x	2 1/2" x	2 3/4"	
	KT010 C and D	2" x	2 1/2" x	3"	
	KT012 C and D	2 1/2" x	2 1/2" x	3 1/4"	
	KT015 C and D	2 1/2" x	2 1/2" x	3 1/2"	
	KT025 C and D	51mm x	63.5mm x	76mm	
	KT032 C and D	51mm x	63.5mm x	76mm	
Material	Top: Reinforced Nylon Swing: Acetal	Bottom: ABS Straight: Acetal			
Lab Tests	Flow Restriction: 41% < standard insert tee	Quick Burst: 2702 kPa @ 62 seconds the pipe failed. KwikTap never failed.			Flow Rate: 51.48 lpm @ 275 kPa
Piping Application	Designed for PE 80 / PE 100 or MDPE Pipe in outdoor irrigation.				
Configurations	Pre-Installed Swing or Drip connections.				
Install Tools Needed	No Tools Needed				
Manufactured In	Colorado, USA				

